


Deltaflux

Top entry

This design is specifically developed when in-line valve maintenance is a crucial request. In this case the valve can be disassembled from the top cover without removing the valve from the pipe. Special tools are usually required for the service activities.



Oil gathering



Topside wellhead



Offshore wellhead



Gas processing

Features	Values
Pressure rating*	ANSI classes from 150 to 1500
Design temperature*	From -46 °C to +200 °C From -51 °F to +392 °F
Nominal sizes*	2" to 48" NPS 50 to NPS 1200
Connections*	<ul style="list-style-type: none"> RF and RTJ flanges as per ASME B16.5, B16.47 and MSS SP-44 Butt welding ends as per ASME B16.25 Hub ends as per customer specifications
End to end dimensions*	ASME B16.10
Construction*	Top entry bolted body
Operator*	<ul style="list-style-type: none"> Bare stem Motor operated (pneumatic, hydraulic, or electric actuator)

(* NOTE: Different functional features and/or materials available on request.
Stated temperature ranges are the maximum for which the standard equipment's full performance is fulfilled.

Table 1 Features

Materials and Approvals

Part	Material
Metallic materials*	<ul style="list-style-type: none"> Low temperature carbon steel (body, connectors**, ball, seats, cover) Stainless steel (stem)
Soft parts*	<ul style="list-style-type: none"> Elastomeric (FKM, HNBR) Graphite
Coatings*	<ul style="list-style-type: none"> Electroless Nickel Plating (ENP, control element) Tungsten Carbide Coating (TCC, seats)

(* NOTE: Different functional features and/or materials available on request.

Stated temperature ranges are the maximum for which the standard equipment's full performance is fulfilled.

(**) NOTE: If necessary, proper material pups can be welded to the valve to fit connecting pipe material.

Table 2 Materials

Product certification:



API 6D
Cert. no.
6D-1170



API 6A
Cert. no.
6A-1252



API 6DSS
Cert. no.
6DSS-0057



IEC 61508 SIL 2
Cert. no.
50 100 13288
REV.005

System certifications:



ISO 9001
Cert. no.
50 100 9927
Rev.006



Pressure Equipment
Directive (PED)
2014/68/EU
Certificate no.
PED-0948-QSH-490-16
REV. 3



ISO 14001
Cert. no.
50 100 13288
REV.005



ISO 45001
Cert. no.
50 100 13322
REV.005

TIV Valves production range has also a wide coverage for fire-safety as per API 607 and API 6FA and for fugitive emissions as per ISO 15848-1. In addition, thanks to a long-term cooperation with international energy companies and EPC contractors, TIV complies with many customers specifications, including design validation procedures.