


Floating valves

Standard

The standard floating ball valve is designed for sweet clean gas applications and moderate minimum and maximum design temperature. This valve configuration is the most competitive in term of price and lead-time.



Floating units



Gas processing



Oil gathering



Green gas production



Gas transmission HP



Gas distribution MP



Gas distribution LP

Features	Values
Pressure rating*	ANSI classes from 150 to 900
Design temperature*	From -29 °C to +150 °C From -20 °F to +302 °F
Nominal sizes*	2" to 36" NPS 50 to NPS 900
Connections*	RF and RTJ flanges as per ASME B16.5, B16.47 and MSS SP-44
End to end dimensions*	ASME B16.10
Construction*	Side entry bolted body
Operator*	<ul style="list-style-type: none"> Bare stem Gear operated Motor operated (pneumatic, hydraulic, gas over oil or electric actuator)

(*) REMARK: Different functional features and/or materials available on request. Stated temperature ranges are the maximum for which the standard equipment's full performance is fulfilled.

Table 1 Features

Materials and Approvals

Part	Material
Metallic materials*	<ul style="list-style-type: none"> • Low temperature carbon steel (body, ball, seats, cover) • Stainless steel (stem)
Soft parts*	<ul style="list-style-type: none"> • Polymeric (Devlon-V) • Elastomeric (FKM, HNBR) • Graphite
Coatings*	Electroless Nickel Plating (ENP)

(*) REMARK: Different functional features and/or materials available on request. Stated temperature ranges are the maximum for which the standard equipment's full performance is fulfilled.

Table 2 Materials

Product certification:



API 6D
Cert. no.
6D-1170



API 6A
Cert. no.
6A-1252



API 6DSS
Cert. no.
6DSS-0057



IEC 61508 SIL 2
Cert. no.
50 100 13288
REV.005

System certifications:



ISO 9001
Cert. no.
50 100 9927
Rev.006



Pressure Equipment
Directive (PED)
2014/68/EU
Certificate no.
PED-0948-QSH-490-16
REV. 3



ISO 14001
Cert. no.
50 100 13288
REV.005



ISO 45001
Cert. no.
50 100 13322
REV.005

TIV Valves production range has also a wide coverage for fire-safety as per API 607 and API 6FA and for fugitive emissions as per ISO 15848-1. In addition, thanks to a long-term cooperation with international energy companies and EPC contractors, TIV complies with many customers specifications, including design validation procedures.